

Most Popular Door Sizes

Call Size	Nominal Width	Nominal Height
3068	3'0" (36 inch)	6'8" (80 inch)
3070	3'0" (36 inch)	7'0" (84 inch)

Door Sizes | 6'8" Height

Call Size	Nominal Width	Nominal Height
2068	2'0" (24 inch)	6'8" (80 inch)
2468	2'4" (28 inch)	6'8" (80 inch)
2668	2'6" (30 inch)	6'8" (80 inch)
2868	2'8" (32 inch)	6'8" (80 inch)
21068	2'10" (34 inch)	6'8" (80 inch)
3468	3'4" (40 inch)	6'8" (80 inch)
3668	3'6" (42 inch)	6'8" (80 inch)
3868	3'8" (44 inch)	6'8" (80 inch)
4068	4'0" (48 inch)	6'8" (80 inch)

Door Sizes | 7'0" Height

Call Size	Nominal Width	Nominal Height
2070	2'0" (24 inch)	7'0" (84 inch)
2470	2'4" (28 inch)	7'0" (84 inch)
2670	2'6" (30 inch)	7'0" (84 inch)
2870	2'8" (32 inch)	7'0" (84 inch)
21070	2'10" (34 inch)	7'0" (84 inch)
3470	3'4" (40 inch)	7'0" (84 inch)
3670	3'6" (42 inch)	7'0" (84 inch)
3870	3'8" (44 inch)	7'0" (84 inch)
4070	4'0" (48 inch)	7'0" (84 inch)

Door Sizes | 8'0" Height

Call Size	Nominal Width	Nominal Height
2080	2'0" (24 inch)	8'0" (96 inch)
2480	2'4" (28 inch)	8'0" (96 inch)
2680	2'6" (30 inch)	8'0" (96 inch)
2880	2'8" (32 inch)	8'0" (96 inch)
21080	2'10" (34 inch)	8'0" (96 inch)
3480	3'4" (40 inch)	8'0" (96 inch)
3680	3'6" (42 inch)	8'0" (96 inch)
3880	3'8" (44 inch)	8'0" (96 inch)
4080	4'0" (48 inch)	8'0" (96 inch)

Actual **width** is 1/4" under nominal door size, to allow for 1/8" clearance on hinge and strike sides.

Actual **height** is 7/8" under nominal door size. Standard undercut is 3/4" + 1/8" clearance at top = 7/8"

All doors = 1-3/4" thickness

*Custom Door Widths and Heights upon Request.

Specifications

Door Thickness

1-3/4" Standard

Core

Rigid Honeycomb Core or Polystyrene Core

Sizes

Standard Widths up to 4'0", Height up to 8'0" (Custom Sizes Available)

Edges

Square Hinge and Lock Edges (Beveled Edges Available) – Full Height, Epoxy Filled Mechanical Interlock Edges

Level

Heavy Duty, SDI Level 2 – 18-Gauge Steel Face Sheets

Standard Preps

161 (cylindrical lock), 86 Edge (mortise lock), Deadbolt, RPD (blank edge, panic reinforced)

Fire-Rating

20-minute, 45 minute, 60 minute, 90 minute and 3 Hour Fire rating

ANSI Standards

Meets or Exceeds Standards for ANSI 250.4 and ANSI 250.8

Optional Preps

Exit Device Trim, Deadbolts, Lite and Louver Cutouts, Continuous Hinge Application (Undersized Width)

Door Finish

Factory-Applied, Baked-On, Rust Inhibiting Gray Primer

(No Special Color Options) – Not intended to be a finish coat. It is recommended that finish paint (topcoat) be applied after installation

Reinforcements

Heavy Gauge Door Closer and Hinge Reinforcements

Channels

14-Gauge Inverted Top and Bottom Channels, Optional Flush Top Cap

Handing

Non-Handed Design; Reversible Hinge Plates

Mfg. Hinge/Lock Locations

Steelcraft, Curries, DKS, Custom Locations

Knock Down Metal Door Frame



For Drywall

(16-gauge Galvanized Steel, Precision die-cut corners with positive locking tabs to assure rigid assembly connections. For masonry, wood, or metal stud walls) Up to 3HR Fire Rating



For Block wall

(16-gauge Galvanized Steel Precision die-cut Corners with positive locking tabs to assure rigid assembly connections) Up to 3HR Fire Rating

Welded Metal Door Frame



For Drywall

(16-gauge Galvanized Steel, Precision die-cut corners with positive locking tabs to assure rigid assembly connections. For masonry, wood, or metal stud walls)



For Block wall

(16-gauge Galvanized Steel Precision die-cut Corners with positive locking tabs to assure rigid assembly connections) Up to 3HR Fire Rating

Lwd also offers a variety of commercial doors and hardware. Call for a quote today!